



## www.smartRdistribution.com orders@smartRdistribution.com

### GS705-35 Gem GS705-35 Shear Aligning Electromagnetic Lock



#### Description

The Gem GS705-35 Shear Aligning Electromagnetic Lock is the ideal solution for demanding security applications. This innovative lock offers unparalleled holding force, automatic misalignment correction, and a concealed mechanism for a sleek and secure aesthetic. With its versatility, reliable operation, and a range of features, the Gem GS705-35 is the perfect choice for securing various door types and enhancing the overall security of your premises.

#### Key Features:

- Superior Shear Holding Force: Delivers an impressive 2,200lbs of holding force for maximum door security.
- Automatic Misalignment Correction: Eliminates the need for perfect door alignment, ensuring reliable locking even with slight
- Concealed Mechanism: Provides a clean aesthetic that complements any architectural style.
- Suitable for Narrow Frames, Double Swing Doors, and Glass **Doors:** Offers exceptional versatility for various door applications.
- Fail-Safe Operation: For safety, the lock automatically releases when power is lost.
- Horizontal or Vertical Installation: Provides flexibility for different door placements.
- Surface, Mortise, or Semi-Mortise Mounting: Allows for a variety of installation options.
- Door Status Monitoring (Optional): Provides real-time confirmation of door lock status (available with built-in bond sensor).
- Adjustable Armature Screws: Accommodates wider door gaps for a secure fit.
- Special Push-Off Device: Eliminates residual magnetism, ensuring effortless door opening.
- Wide Operating Temperature Range: Functions reliably in temperatures from -30°C to +50°C.



**Smart R Distribution Limited** 

Smart R House · 13 Moonhall Business Park · Helions Bumpstead Road Haverhill · Suffolk · CB9 7AA · England Phone UK: 01440 704 387 Phone Int'l: +44 1440 704 387

"Putting the right pieces together"



# 01440 704 387

# www.smartRdistribution.com orders@smartRdistribution.com

### **Product Specifications**

Weight	2200 kg
Brand	GEM
Power-requirement	12-24 VDC
Operating-temperature	-30°C to 50°C
Mounting	Horizontal, Vertical
Safety-features	Fail-Safe
Lock-options	Monitored

