

SR1-REL-310-1224

SR1-REL-310-1224 Selectable Voltage 12/24VDC Electric Release with selectable Fail-Secure / Fail-Safe Operation

Description

Dual-Voltage ANSI-Style Electric Release 12 / 24 VDC Selectable - with Long & Short Faceplates



- For wooden and metal door frames
- Fail-safe / fail-secure selectable operation - very simple screw position selection
- Voltage: 12 VDC or 24 VDC - selectable
- Voltage tolerance: $\pm 15\%$
- Current: 0.28A @ 12 VDC, 0.14A @ 24 VDC (at temperature 20°C)
- Operating Temperature: -10°C to +45°C
- Humidity: 0% to 95% non-condensing
- Faceplate material: stainless steel
- Greater than 900Kg (2000) Lbs jaw strength pull testing
- Dimensions (Long Faceplate): 202mm (L) x 36.5mm (W) unit depth 33mm
- Dimensions (Short Faceplate): 124mm (L) x 36.5mm (W) unit depth 33mm
- Approximate shipping weight (Long Faceplate): 625g
- Approximate shipping weight (Short Faceplate): 490g

Smart R Distribution Limited

Smart R House · 13 Moonhall Business Park · Helions Bumpstead Road
Haverhill · Suffolk · CB9 7AA · England
Phone UK: 01440 704 387
Phone Int'l: +44 1440 704 387

"Putting the right pieces together"

Product Specifications

Weight	380 kg
Brand	GEM
Voltage	12VDC or 24VDC Selectable
Safety-features	Fail-Safe, Fail-Secure
Form-factor	Electric Strike