

SR1-MAG-600FSF

SR1-MAG-600FSF 500Lb (2220N) Stainless Steel Maglock – Monitored



Description

Suitable for outside installations or areas where the magnet may be affected by moisture, such as vehicle and pedestrian single gates. The magnet enclosure has mounting holes which allow for side or face fixing to the door frame. **Features & Benefits**

- Surface mounted and easy to install
- Stainless steel housing
- Both side and face fixing options available
- Reed switch monitoring
- 12 or 24V DC Operating voltage - selectable at installation via wiring configuration (instructions included)
- Cable entry point features an M20 threaded collar to allow for watertight fixing with suitable conduit
- Current draw 500mA at 12V / 250mA at 24V
- Magnet Dimensions: 222mm (L) x 63mm (W) x 40mm (D)

Smart R Distribution Limited

Smart R House · 13 Moonhall Business Park · Helions Bumpstead Road
Haverhill · Suffolk · CB9 7AA · England
Phone UK: 01440 704 387
Phone Int'l: +44 1440 704 387

"Putting the right pieces together"

Product Specifications

Weight	2000 kg
Brand	Smart R Distribution
Holding-force	500 Lbs
Material	Stainless Steel
Contacts	1-pole changeover (1 x SPDT)
Voltage	12VDC or 24VDC Selectable