



## www.smartRdistribution.com orders@smartRdistribution.com

## SRB-YNL-200H BQT YD30D Motorised Side-Load Lock For Swing-Through And Single Swing Doors



#### Description

The YD30D Cobalt sets a new standard for electronic door locks. This innovative system delivers unmatched security, automatic misalignment correction, secure sideload release, and versatile installation options. The BQT YD30 is the ideal solution for demanding applications where exceptional performance and reliability are paramount.

#### Key Features:

- High-Security Locking: Two 10mm thick stainless steel bolt pins provide a holding force exceeding 10,000N, ensuring exceptional security.
- Automatic Misalignment Correction: The Cobalt's unique pivot action automatically corrects misalignment up to 8mm in either direction, guaranteeing a secure lock even on imperfect door
- Secure Sideload Release: The collapsing mechanism unlocks reliably even with a forceful push (up to 1,000N) on the door, ensuring a safe exit.
- Complete Monitoring: The YD30D Cobalt provides both door position and bolt position as monitor signals, offering comprehensive system control.
- Low-Current Consumption: Draws minimal power (40mA standby, 300mA operation) for energy-efficient operation.
- Integrated Access Control: Selectable fail-safe and fail-secure modes, along with multiple lock/unlock attempts, allow for seamless integration with various access control systems.
- Versatile Installation: Includes fitting tabs for mortise mounting in both the side and top of door frames. Optional housing and dress plate enable surface mounting for broader application, including glass doors.



**Smart R Distribution Limited** 

Smart R House · 13 Moonhall Business Park · Helions Bumpstead Road Haverhill · Suffolk · CB9 7AA · England Phone UK: 01440 704 387 Phone Int'l: +44 1440 704 387

"Putting the right pieces together"



# 01440 704 387

# www.smartRdistribution.com orders@smartRdistribution.com

### **Product Specifications**

Weight	600 kg
Brand	BQT Solutions
Construction	Stainless Steel
Mounting	Flush Mount
Power-requirement	12-24 VDC
Lock-options	Monitored
Safety-features	Fail-Safe, Fail-Secure

