

SR1-BGS-303-LSRC

CP3-LSRC: Low Profile Resettable Triple Pole Emergency Break Glass

Description

The CP3-LSRC is a highly visible and easily resettable triple pole emergency break glass unit (BGU) designed for critical emergency door release applications. Finished in green and suitable for surface mounting, this unit provides a reliable and compliant solution for access control and emergency egress.

Key Features:

- **Triple Pole Configuration:** For flexible wiring and integration with various security and access control systems.
- **Resettable Mechanism:** Easily reset the CP3-LSRC after activation using the key supplied, eliminating the need for replacement glass and reducing maintenance costs.
- **Integrated Sounder:** Includes an adjustable sounder to provide an audible alert upon activation, drawing immediate attention to the emergency.
- **Bi-Coloured LED Indicators:** Features adjustable dual-colour LEDs (Green and Red) to clearly indicate the unit's status (e.g., armed, activated).
- **Low Profile Design:** Compact size (85mm x 85mm x 42mm excluding cover) for discreet surface mounting.
- **Protective Cover:** Supplied as standard to prevent accidental activation.
- **Single Gang Mounting:** Fits standard single gang electrical boxes for straightforward installation.
- **Wide Power Compatibility:** Operates on 12Vdc or 24Vdc power supplies.
- **High Contact Load:** Contacts rated at 125V/3A for reliable switching.



Smart R Distribution Limited

Smart R House · 13 Moonhall Business Park · Helions Bumpstead Road
Haverhill · Suffolk · CB9 7AA · England
Phone UK: 01440 704 387
Phone Int'l: +44 1440 704 387

"Putting the right pieces together"

Product Specifications

Weight	245 kg
Colours	Green
Connection-type	Terminal connection
Construction	Plastic
Contacts	1-pole changeover (1 x SPDT), 2-pole changeover (2 x SPDT), 3-pole changeover (3 x SPDT)
Mounting	Surface Mount
Power-requirement	12-24 VDC, 45mA