



www.smartRdistribution.com orders@smartRdistribution.com

ACT5 Acre ACT5 Codelock Keypad – 1 Door and Up to 10 Users



Description

The Acre ACT5 Codelock Keypad is a reliable and stylish standalone access control solution designed for single-door applications. Featuring a robust IP55-rated polycarbonate housing with durable stainless steel keys and potted electronics, the ACT5 is built for dependable performance in both indoor and outdoor environments.

Key Features:

- Standalone Codelock: Thye ACT5 keypad manages access for one door independently, without requiring connection to a central control panel.
- 10 User PIN Codes: Supports up to 10 unique user PIN codes, making it suitable for small offices, individual units, or restricted
- Durable Construction: Housed in a stylish and robust IP55-rated polycarbonate casing, offering protection against dust and splashes of water.
- Stainless Steel Keys: Ensures longevity and resistance to wear, even with frequent use.
- Potted Electronics: Provides enhanced protection against moisture and environmental factors, making it ideal for outdoor installation.
- Versatile Mounting: Supports both surface and flush mounting options for flexible installation.
- Wide Operating Voltage: Compatible with 12 24 Volts AC/DC power supplies.
- Low Power Consumption: Efficient operation with a nominal current consumption of 30mA and a maximum of 120mA.
- Wide Operating Temperature: Functions reliably across a broad temperature range from -40°C to +70°C.
- Compact Dimensions: Measures 94 x 130 x 25mm, allowing for discreet placement

Please see the ACT5-EM for version with a Card/Fob Reader included



Smart R Distribution Limited

Smart R House · 13 Moonhall Business Park · Helions Bumpstead Road Haverhill · Suffolk · CB9 7AA · England Phone UK: 01440 704 387 Phone Int'l: +44 1440 704 387

"Putting the right pieces together"



01440 704 387

www.smartRdistribution.com orders@smartRdistribution.com

Product Specifications

Weight	0 kg
Brand	ACRE
Keypad	Backlit, Integral Keypad
Mounting	Flush Mount, Surface Mount
Power-requirement	12-24 VDC/VAC
Output-relays	1
Construction	Metal
Operating-temperature	-40°C to 70°C
Access-control-system-type	Standalone Keypads

