

A-ISO-VP

Authenticard A-ISO PVC Printable Proximity / Smart Card (ISO7810-Compliant)

**Description**

The Authenticard "A-ISO" card is available in the popular choice of 125KHz and 13.56MHz technologies. Being ISO7810 compliant with a nominal thickness of 0.762mm (030") to meet the requirements of all good card printers, the card features a gloss-white graphics quality surface optimised for Photo-ID printing on both sides.

The Authenticard "A-ISO" card is available in 125KHz proximity, MIFARE S50 1K, MIFARE S70 4K, DESFire 4K, DESFire 8K, or LEGIC technologies.

- Optional custom printing / personalisation (see our Card Services section)
- 125KHz models work with Authenticard 125, HID Proximity, Farpointe Data and EM410x readers
- FPR versions are Field Programmer Ready for encoding with your own field programmer
- LFO versions are encoded with open format data e.g. 26-Bit Wiegand
- Matching external printed card number (other printing options available)
- Composite construction available - please call for more information



**Smart R Distribution Limited**

Smart R House · 13 Moonhall Business Park · Helions Bumpstead Road  
Haverhill · Suffolk · CB9 7AA · England  
Phone UK: 01440 704 387  
Phone Int'l: +44 1440 704 387

*"Putting the right pieces together"*

## Product Specifications

Weight	6 kg
Brand	Authenticard
Colours	White
Frequency	125 kHz (RFID), 13.56 MHz
Construction	PVC, PVC/PET
Versions	D8, FPR, L8, LFO, LFP, M1, M4
Form-factor	Cards
Programming	CSN (Chip Serial Number), Secure Sector, Unprogrammed, Custom, Open, Multi-Factor
Reader-and-card-technology	Unprogrammed, Custom EM (125 kHz), EM Proximity (125 kHz), MIFARE, DESFire, HID iCLASS, HID Seos, Legic