

SR1-MAG-12002-VP

Dual Standard Maglock – Up To 1200lb (545Kg) Holding Force x 2



Description

Dual version of our SR1-MAG-1200 Standard Maglock A surface-mounted "face to face" dual electromagnetic lock offering up to 2 x 545 Kg (2 x 1200 Pounds) holding force. This lock is intended for internal double out-swing doors. Installation on in-swing doors, glass doors and narrow-style frames will require additional brackets. Available in the following versions (please select when ordering): **Standard Version** - no outputs
Door-Status Output - features a door-status sensor for applications requiring a door-status signal
Door-Status & Monitor Output - for applications requiring monitoring of the armature plate in contact with the maglock and also a door-status signal

Product Specifications

Weight	9500 kg
Maglock-options	<i>Standard Unmonitored, With Door Status Sensor, With Monitor Output and Door Status Sensor</i>
Connection-type	<i>Terminal connection</i>
Material	<i>Aluminium Alloy</i>
Holding-force	<i>1200 Lbs x 2</i>
Mounting	<i>Surface Mount</i>
Operating-temperature	<i>-10°C to 55°C</i>
Voltage	<i>12-24 VDC</i>
Brand	<i>Smart R Distribution</i>
Variations	,

Smart R Distribution Limited

Smart R House · 13 Moonhall Business Park · Helions Bumpstead Road
Haverhill · Suffolk · CB9 7AA · England
Phone UK: 01440 704 387
Phone Int'l: +44 1440 704 387

"Putting the right pieces together"