

SR1-MAG-12002-VP

Standard Unmonitored Double Maglock With Optional Door Status

**Description**

Our Standard Unmonitored Double Maglock With Optional Door Status offer a dependable and secure solution for double door access control. These maglocks offer exceptional holding force, easy installation, and a stylish design. With the option for door status monitoring, you can choose the level of functionality that best suits your specific security requirements.

**Key Features:**

- **Double-Sided Locking:** Provides a combined holding force of up to 545kg (1200lb) for exceptional security on double doors.
- **High Holding Force per Side:** Delivers 545kg (1200lb) of holding force on each side of the door for reliable locking.
- **Dual Voltage Operation:** Selectable for 12Vdc or 24Vdc power supply compatibility.
- **Surface Mount Installation:** Simple and straightforward for efficient setup.
- **Silver Anodised Aluminium Finish:** Offers a sleek and modern aesthetic.
- **MOV Surge Protection:** Safeguards against electrical spikes and surges.
- **Fail-Safe Operation:** Doors unlock when power is lost, ensuring safe egress.
- **Anti-Residual Magnetism Protection:** Prevents lingering magnetism for reliable locking.
- **Top-Plate, Armature-Plate, and Fixings Included:** Provides all necessary components for installation (excluding power supply).
- **Door Status Monitoring (SKU: SR1-MAG-12002D Only):** Includes reed switch contacts (one per side) to monitor door position (open or closed), ideal for integrating with access control systems for improved security and logging.



**Smart R Distribution Limited**

Smart R House · 13 Moonhall Business Park · Helions Bumpstead Road  
Haverhill · Suffolk · CB9 7AA · England  
Phone UK: 01440 704 387  
Phone Int'l: +44 1440 704 387

*"Putting the right pieces together"*

## Product Specifications

Weight	9500 kg
Lock-options	Unmonitored, Unmonitored + Door Status Sensor
Connection-type	Terminal connection
Construction	Aluminium Alloy
Holding-force	1200 Lbs x 2
Mounting	Surface Mount
Operating-temperature	-10°C to 55°C
Power-requirement	12 VAC, 12-24 VDC, 24 VDC
Brand	Smart R Distribution
Safety-features	Fail-Safe
Form-factor	Double Maglock