

SR1-REX-STA200F

SR1-REX-STA200F Illuminated Infra-Red Exit Button – Architrave-Mount

**Description**

**Infra-Red means not having to touch the button - ideal for applications where the user needs to release a door without physically touching the button e.g. food preparation, clean rooms, laboratories and hospitals.**

This exit button is ideal for applications where the user needs to release a door without physically touching a button e.g. food preparation, clean rooms, laboratories and hospitals. The internal relay is activated when an object enters the detection field, to open the door without encouraging the spread of contamination.



- Material: Stainless Steel
- Finish: Brushed, screen printed "DOOR RELEASE"
- LED "halo" door status indicator
- Rated to IP65 (sensor unit only)
- Operating temperature: -10°C to +70°C
- Operating voltage: 12-24 VDC
- Current requirements: 45 mA.
- Sensor range: Adjustable up to 10cm
- Contacts: Normally Open - Common - Normally Closed (SPDT)
- Contact rating: 3A @ 125 VAC / 30 VDC
- Adjustable relay timer period (0.5 -20 seconds) or toggle mode
- Dimensions: H85 x W40 x D30 mm

**Smart R Distribution Limited**

Smart R House · 13 Moonhall Business Park · Helions Bumpstead Road  
Haverhill · Suffolk · CB9 7AA · England  
Phone UK: 01440 704 387  
Phone Int'l: +44 1440 704 387

*"Putting the right pieces together"*

## Product Specifications

Weight	kg
Mounting	Flush Mount
Legend	DOOR RELEASE
Voltage	12-24 VDC, 45mA
Operating-temperature	-10°C to 70°C
Material	Stainless Steel
Brand	Smart R Distribution