

Signo40  
HID Signo Model 40 Wallswitch Reader

**Description**



HID Signo readers are available in four base models – 20, 20K, 40 and 40K. The HID Signo Reader 40 is a founding member of the Signo platform. Offering a truly dynamic approach to secure electronic access control, HID Signo Readers are designed to be highly versatile, powerful, and connected for the future. A perfect fit for door applications requiring a wallswitch-style card reader, the HID Signo Reader 40 supports a range of different credential technologies including mobile access – please select your choice when ordering. If you need assistance in identifying the correct option for your application then please contact us! Signo Model 40 is available in the following configurations (please select when ordering) :

- 40TKS-00-000000 wallswitch-mount multitech reader “Standard Profile”, Terminal Connection
- 40NKS-00-000000 wallswitch-mount multitech reader “Standard Profile”, Pigtail Connection
- 40TKS-01-000000 wallswitch-mount reader “SEOS Profile” (only reads iCLASS cards), Terminal Connection
- 40NKS-01-000000 wallswitch-mount reader “SEOS Profile” (only reads iCLASS cards), Pigtail Connection
- 40TKS-02-000000 wallswitch-mount reader “Smart Profile”, Terminal Connection
- 40NKS-02-000000 wallswitch-mount reader “Smart Profile”, Pigtail Connection
- 40TKS-T0-000000 wallswitch-mount reader “Priority Standard Profile”, Terminal Connection

## Product Specifications

Weight	140 kg
Brand	HID
Frequency	125 KHz, 13.56 MHz, 2.45 GHz
Mounting	Surface Mount
Colours	Black
Voltage	12 VDC, 250 mA
Annunciation	Sounder, Tri-Colour LED
Operating-temperature	-35°C to 66°C
Protection-rating	IP65
Output-protocol	Clock & Data, OSDP, Wiegand
Material	Polycarbonate
Variations	,