

01440 704 387

www.smartRdistribution.com orders@smartRdistribution.com

COM-6602W



Description

PRODUCT CODE: 6602W Colour monitor with audio induction loop, 4.3" / 16:9 touch screen and hands-free full-duplex audio. Introducing the Comelit 6602W, a 4.3"/16:9 hands-free colour monitor with an audio induction loop for hearing aid users. This Icona monitor boasts a touch screen and full-duplex audio, offering control over backlighting, contrast, audio, and ringtone volumes, and comes equipped with touch-sensitive capacitive buttons for lock-release, audio activation, and more, along with LEDs for door status. This device supports floor door call management, alarm inputs, and micro SD card functionality (SD card not included). It's customisable for ringtones, video memory, and absence messages. Plus, it works seamlessly on standard PoE systems.

- 4.3-inch touchscreen display
- Built-in induction loop for hearing aid users
- Privacy function
- 7 programmable buttons
- Hands-free audio
- Colour video
- Door lock release button
- Volume control
- Brightness control
- Wall mountable

*Installation requires a flush-mount box for plasterboard (p/n 6617), standard flush-mount box (p/n 6117) or surface-mount box (p/n 6120) that is not included with the Icona monitor.



Smart R House · 13 Moonhall Business Park · Helions Bumpstead Road Haverhill · Suffolk · CB9 7AA · England Phone UK: 01440 704 387 Phone Int'l: +44 1440 704 387

"Putting the right pieces together"



01440 704 387

www.smartRdistribution.com orders@smartRdistribution.com

Product Specifications

BrandComelit-PACColoursWhite and GreyConstructionABS, GlassPower-requirementPoEProtection-ratingIP30Operating-temperature5°C to 40°CMountingFlush Mount, Surface MountDoor-entry-system-componentAncillary ProductsMonitor-or-handset-typeVideo Handsfree	Weight	500 kg
ConstructionABS, GlassPower-requirementPoEProtection-ratingIP30Operating-temperature5°C to 40°CMountingFlush Mount, Surface MountDoor-entry-system-componentAncillary Products	Brand	Comelit-PAC
Power-requirementPoEProtection-ratingIP30Operating-temperature5°C to 40°CMountingFlush Mount, Surface MountDoor-entry-system-componentAncillary Products	Colours	White and Grey
Protection-rating Operating-temperature 5°C to 40°C Mounting Flush Mount, Surface Mount Door-entry-system-component Ancillary Products	Construction	ABS, Glass
Operating-temperature5°C to 40°CMountingFlush Mount, Surface MountDoor-entry-system-componentAncillary Products	Power-requirement	PoE
Mounting Flush Mount, Surface Mount Door-entry-system-component Ancillary Products	Protection-rating	IP30
Door-entry-system-component Ancillary Products	Operating-temperature	5°C to 40°C
	Mounting	Flush Mount, Surface Mount
Monitor-or-handset-type Video Handsfree	Door-entry-system-component	Ancillary Products
	Monitor-or-handset-type	Video Handsfree
System-type Video	System-type	Video

