



www.smartRdistribution.com orders@smartRdistribution.com

SPC-WPIR-EXT AM Acre WPIR-EXT AM – Pet-Immune Exterior PIR Detector



Description

The Acre WPIR-EXT AM is a double quad zone exterior PIR detector designed to deliver exceptional security for your clients' properties. This innovative solution seamlessly integrates with the SPC control panel system, providing reliable intrusion detection and pet immunity for comprehensive outdoor security.

Key Features:

- Double Quad Detection: The Acre WPIR-EXT AM Offers a wide detection range of 3 to 12 meters for comprehensive outdoor area coverage.
- Pet Immunity Up to 25kg: Reduces false alarms caused by pets weighing up to 25kg, ensuring accurate detection of human
- Adaptable Configuration: Mechanical dip switches and "over-theair" firmware configuration allow for customisation of sensitivity, LED behaviour, walk test settings, supervision time, and more.
- Durable Construction: Built to withstand harsh environments with an IP65 weatherproof rating.
- Long Battery Life: Up to 5 years of operation with highperformance lithium batteries and Automatic Power Save (APS) technology.
- Extended Range: Communicates reliably with the SPC transceiver from up to 500 meters away in open space.
- Simplified Installation: Easy to mount on corners, walls, or poles with full tamper protection for maximum security.
- Effortless Pairing: Smart pairing mechanism with automatic pairing on battery insertion ensures a quick and hassle-free setup.
- Informative LED Indicators: LED and internal buzzer provide clear guidance during walk testing and system status updates.



Smart R Distribution Limited

Smart R House · 13 Moonhall Business Park · Helions Bumpstead Road Haverhill · Suffolk · CB9 7AA · England Phone UK: 01440 704 387 Phone Int'l: +44 1440 704 387

"Putting the right pieces together"



01440 704 387

www.smartRdistribution.com orders@smartRdistribution.com

Product Specifications

Weight	500 kg
Brand	ACRE
Series	SPC
Device-type	PIR Detector (Pet Tolerant)
Protection-rating	IP65
Power-requirement	4 x AA Battery
Operating-temperature	-25°C to 55°C
Connection-type	Wireless

