



www.smartRdistribution.com orders@smartRdistribution.com

A-PD4-VP

Authenticard A-PD4: Dual Frequency Access Control Card (125kHz Prox and MIFARE DESFire 4K EV2)



Description

The Authenticard A-PD4 is a versatile and secure dual frequency access control card that offers a range of benefits for businesses and organisations seeking to enhance their security and streamline access management. With its customisable options, durable construction, and advanced technology, the Authenticard A-PD4 is an ideal choice for various applications.

Key Features:

- **Dual Frequency Technology:** Supports both 125 kHz proximity and MIFARE DESFire 4K EV2 for compatibility with existing systems and advanced security features.
- Customisable Encoding: Choose from different encoding options to suit your specific requirements (LFP: custom format, LFO: 26-bit
- Unprogrammed Format: Allows for flexible programming and customisation of card data.
- Durable Construction: PVC construction ensures durability and resistance to wear and tear.
- Gloss White Finish: Professional and clean appearance.
- **ID-1 Format:** Adheres to ISO 7810 standards for compatibility with standard card readers.
- Printable Surfaces: Personalise cards with company logos, employee information, or other details.

Note: The specific encoding option (LFP, LFO, or unprogrammed) should be selected based on your system's requirements and desired level of customisation. Please contact us for any assistance if selecting the best product for your needs.



Smart R Distribution Limited

Smart R House · 13 Moonhall Business Park · Helions Bumpstead Road Haverhill · Suffolk · CB9 7AA · England Phone UK: 01440 704 387 Phone Int'l: +44 1440 704 387

"Putting the right pieces together"



01440 704 387

www.smartRdistribution.com orders@smartRdistribution.com

Product Specifications

Weight	6 kg
Brand	Authenticard
Colours	White
Frequency	125 kHz (RFID), 13.56 MHz, Dual Frequency
Construction	PVC
Form-factor	Cards
Programming	Unprogrammed, Custom, Open
Reader-and-card-technology	Proximity (125 kHz), Custom EM (125 kHz), EM Proximity (125 kHz), HID Prox (125 kHz), Indala Proximity (125 kHz), Paxton Proximity (125 kHz), MIFARE, DESFire, HID iCLASS, HID Seos, Legic

