

WP66-G-VP

RGL WP66-G Series – Externally Rated Exit Button with Choice of Legend

Description

The RGL WP66-G is a highly durable and reliable externally rated exit button, designed for robust performance in demanding outdoor or indoor environments. Featuring a large green dome button and an impressive IP66 weatherproof rating, this unit provides a clear and dependable point of egress, with the flexibility to choose a legend that perfectly suits your application.

Key Features:

- **Externally Rated (IP66):** Offers superior ingress protection against dust and powerful water jets, making it ideal for outdoor installations and harsh indoor environments.
- **Momentary Operation:** Provides momentary contact (N/O - N/C), ensuring the circuit is activated only while the button is pressed.
- **Double Pole Contacts:** Equipped with double pole normally open (N/O) and normally closed (N/C) contacts, offering versatile wiring options for various access control or alarm systems.
- **High Output Rating:** Contacts are rated for 4 AMP @ 30V AC/DC, capable of handling a wide range of locking devices and control circuits.
- **Robust Construction:** Housed in a high-impact, two-part cross-polymer enclosure, ensuring longevity and resistance to physical wear.
- **Integrated Conduit Knockouts:** Features pre-moulded M16/20 conduit knockouts for straightforward and neat cable entry.
- **Silver Contacts:** Ensures reliable electrical conductivity and a long operating life (1,000,000 mechanical cycles).

Contents:

- 1 x Green Dome Exit Button
- 4 x Screws
- 1 x Surface Enclosure (integrated)



Product Specifications

Weight	248 kg
Brand	RGL
Construction	Polymer
Contacts	2-pole contact
Protection-rating	IP66
Mounting	Surface Mount
Legend	DOOR RELEASE, PRESS TO EXIT, Gate Release, Push To Open
Operating-temperature	-20°C to 60°C