



www.smartRdistribution.com orders@smartRdistribution.com

BAS-IP-AA-07FBI-VP BAS-IP AA-07FBI: Multi-Resident Entrance Panel with Facial Recognition

Description

The BAS-IP AA-07FBI is a high-performance, multi-resident entrance panel offering advanced access control and communication features, including face recognition and support for BAS-IP UKEY mobile access. Accredited by Secured By Design, this panel is built with a highly vandalresistant stainless steel body and incorporates vital accessibility features like external induction loop connectivity for the hearing impaired.

Key Features:

- Secured By Design Approved
- Vandal-Resistant Stainless Steel Body: Crafted from 3mm thick AISI 304 stainless steel (BAS-IP AA-07FBI-SS), ensuring exceptional durability and resistance to vandalism, making it ideal for demanding public environments.
- 4.3" Backlit TFT Color Screen: Provides clear visual feedback and navigation for users.
- High-Resolution IP Camera: Features a 1/3" 2 MP camera with a wide 110° horizontal viewing angle, delivering Full HD (1920x1080) video output (H.264 Main Profile) for sharp image quality.
- Enhanced Night Vision: Equipped with 6 LEDs for effective night backlight, ensuring clear visibility even in low light conditions (0.01 LuX minimum illumination).
- Comprehensive Access Methods: Supports a multitude of secure and convenient ways to open the lock:
 - o From the indoor monitor.
 - Via guest link, QR code, or access code.
 - o By access card, license plate recognition.
 - Advanced Face ID recognition.
 - Through BAS-IP Intercom and UKEY mobile apps.
 - o From the web interface.
- External Induction Loop Connectivity

Available In The Following Finishes:

- BAS-IP AA-07FBI-SS: Stainless Steel Finish
- BAS-IP AA-07FBI-S: Silver Finish



Smart R Distribution Limited

Smart R House · 13 Moonhall Business Park · Helions Bumpstead Road Haverhill · Suffolk · CB9 7AA · England Phone UK: 01440 704 387 Phone Int'l: +44 1440 704 387

"Putting the right pieces together"



01440 704 387

www.smartRdistribution.com orders@smartRdistribution.com

Product Specifications

Weight	kg
Brand	,
Brand	Bas-IP, Secured By Design
Protection-rating	IP65
Mounting	Flush Mount, Surface Mount (Box Required)
Operating-temperature	-40°C to 65°C
Number-of-users	10,000+
Colours	Stainless Steel, Silver
Power-requirement	12 VDC, PoE
System-type	Video
Door-entry-system-component	Entrance Panel
Device-type	Entrance Panel
Construction	Aluminium
Keypad	Illuminated Keypad

