

STEALTH01-VP

STEALTH01 Series: Unmonitored Slim Mag Locks with Optional Door Status



Description

The STEALTH01 series offers a compact, high-performance, and secure solution for single-door access control. These slimline, unmonitored magnetic locks provide a robust 600lb (275kg) of holding force, making them ideal for a wide range of indoor applications. With a modern stealth black finish and fire-rated construction, the series is available in two variations: the standard STEALTH01, and the STEALTH01DS, which includes the additional feature of door position monitoring.

Technical Specifications:

- **Holding Force:** Up to 275kg (600lb)
- **Current Draw:** 500mA @ 12Vdc / 250mA @ 24Vdc
- **Voltage Tolerance:** +/- 15%
- **Operating Temperature:** -10°C to +55°C
- **Humidity:** 0-95% non-condensing
- **Dimensions:** 250mm x 48mm x 26mm (Mag dimension)
- **Weight:** Approx. 2kg
- **Door Status Contact (STEALTH01DS):** Reed switch

Product Specifications

Weight	2000 kg
Brand	Stealth Locking
Lock-options	Unmonitored, Unmonitored + Door Status Sensor
Holding-force	600 Lbs
Mounting	Surface Mount
Operating-temperature	-10°C to 55°C
Power-requirement	12-24 VDC
Safety-features	Fail-Safe, Fire Resistant
Form-factor	Mini Maglock
Fire-rating	Fire Rated
Colours	Black