

STEALTH40-VP

STEALTH40 Series: Monitored Double Standard Maglock with Optional Door Status

**Description**

The STEALTH40 series offers a powerful and secure solution for double doors, providing a formidable 1200lb (545kg) of holding force *per side*. These monitored double magnetic locks are designed for demanding indoor applications and feature a modern stealth black finish for a discreet, professional aesthetic. The series includes two variations, the STEALTH40, which provides essential lock status monitoring, and the STEALTH40DS, which adds the critical function of door position monitoring.

**Technical Information:**

- **Holding Force:** Up to 545kg (1200lb) per side
- **Current Draw:** 500mA @ 12Vdc / 250mA @ 24Vdc
- **Voltage Tolerance:** +/- 15%
- **Operating Temperature:** -10°C to +55°C
- **Humidity:** 0-95% non-condensing
- **Weight:** Approx. 9.6kg
- **Relay Output:** COM/NO/NC (1A @ 24Vdc) per side
- **Door Status Contact (STEALTH40DS):** Reed switch (one per side)

**Product Variations:**

- **STEALTH40:** A standard double monitored magnetic lock, offering a total of 2400lbs of holding force. It provides lock status feedback via a relay and LED indicators.
- **STEALTH40DS:** A standard double monitored magnetic lock that includes integrated door status monitoring contacts to monitor the open or closed position of each door.



## Product Specifications

Weight	kg
Brand	Stealth Locking
Lock-options	Monitored, Monitored + Door Status Sensor
Holding-force	1200 Lbs x 2
Mounting	Surface Mount
Operating-temperature	-10°C to 55°C
Power-requirement	12-24 VDC
Safety-features	Fail-Safe
Form-factor	Double Maglock
Fire-rating	Fire Rated
Colours	Black