

STEALTH10-VP

STEALTH10 Series: Fire Rated Unmonitored Standard Maglock With Optional Door Status Monitoring

**Description**

The STEALTH10 series offers a powerful and secure solution for single-door access control. These standard-sized, unmonitored magnetic locks provide a substantial 1200lb (545kg) of holding force, making them ideal for a wide range of indoor applications. With a modern stealth black finish and fire-rated construction, the series is available in two variations: the standard STEALTH10, and the STEALTH10DS, which includes the valuable feature of door position monitoring.

**Technical Information:**

- **Holding Force:** Up to 545kg (1200lb)
- **Current Draw:** 500mA @ 12Vdc / 250mA @ 24Vdc
- **Voltage Tolerance:** +/- 15%
- **Operating Temperature:** -10°C to +55°C
- **Humidity:** 0-95% non-condensing
- **Weight:** Approx. 4.8kg
- **Door Status Contact (STEALTH 10DS only):** Reed switch

**Product Variations:**

- **STEALTH10:** A standard, unmonitored single magnetic lock, designed for basic, reliable security.
- **STEALTH10DS:** A standard, unmonitored single magnetic lock that includes door status monitoring contacts to monitor the open or closed position of the door.



## Product Specifications

Weight	kg
Brand	Stealth Locking
Lock-options	Unmonitored, Unmonitored + Door Status Sensor
Holding-force	1200 Lbs
Mounting	Surface Mount
Operating-temperature	-10°C to 55°C
Power-requirement	12-24 VDC
Safety-features	Fail-Safe, Fire Resistant
Form-factor	Standard Maglock
Fire-rating	Fire Rated
Colours	Black