



www.smartRdistribution.com orders@smartRdistribution.com

RGL-WP-EBSS25/PTE RGL WP-EBSS25/PTE: Weatherproof Stainless Steel Exit Button



Description

The RGL WP-EBSS25/PTE is a highly durable and reliable "Push to Exit" (PTE) button, specifically designed for use in harsh external and sensitive internal environments. With its robust stainless steel construction, high ingress protection rating, and double-pole contacts, this momentary switch provides a secure and long-lasting method for door release.

Technical Specifications:

- Contacts: Double pole N/O N/C
- Output: 4 AMP contact @ 30V AC/DC
- Ingress Protection: IP65
- Operating Temperature: -20°C to +60°C
- Operating Life (Mechanical): 1,000,000 cycles
- Operating Travel: 2mm
- Contact Resistance: 10m OHM (Max)
- **Dimensions (H x W x D):** 85mm x 85mm x 40/50mm
- Weight (Unboxed): 200g
- Fixing Holes Distance: 60mm



Smart R House · 13 Moonhall Business Park · Helions Bumpstead Road Haverhill · Suffolk · CB9 7AA · England Phone UK: 01440 704 387 Phone Int'l: +44 1440 704 387

"Putting the right pieces together"



01440 704 387

www.smartRdistribution.com orders@smartRdistribution.com

Product Specifications

Weight	200 kg
Brand	RGL
Protection-rating	IP65
Contacts	2-pole contact
	,
Mounting	Flush Mount, Surface Mount
Legend	Push To Open
Colours	Black, Stainless Steel
Construction	Stainless Steel
Device-type	Exit Button



"Putting the right pieces together"