

XPR-XPM-MF-VP

XPR XPM-MF Series: Slim 13.56 MHz RFID Reader (Weigand or OSDP Output)

### Description

The XPR XPM-MF-X is a slimline 13.56 MHz RFID reader from the XPRO Series, designed for modern access control systems requiring a discreet yet powerful solution. Compact and elegant, this mullion-mount reader supports Mifare CSN, DESFire, and Xsecure encrypted credentials, offering secure authentication for a wide range of applications. Compatible with both Weigand and OSDP communication, the XPM-MF-X delivers flexibility, high performance, and long-term reliability for installers and system integrators.

#### Technical Specifications:

- **Mounting:** Surface-mounted
- **Housing:** Polycarbonate copolymer (UL94)
- **Internal buzzer:** Volume adjustable via software
- **Protocol:** Wiegand, OSDP
- **Read range:** Up to 9 cm (depending on card type and size)
- **Operating frequency:** 13.56 MHz
- **Tamper protection:** Yes
- **Wiring:** Terminal block (standard)
- **Operating voltage:** 9 - 15 V DC
- **Max. current consumption at 12 V DC:** 100 mA
- **Supported credentials:** Xsecure, Mifare CSN (Classic, DESFire, Plus, Ultralight), Mifare DESFire (EV1, EV2, EV3)

### Pack Contents

- 1 × XPR XPM-MF-X RFID Reader
- 1 × Mounting kit and screws
- 1 × Quick installation guide
- 1 × Xsecure® key



#### Smart R Distribution Limited

Smart R House · 13 Moonhall Business Park · Helions Bumpstead Road  
Haverhill · Suffolk · CB9 7AA · England  
Phone UK: 01440 704 387  
Phone Int'l: +44 1440 704 387

*"Putting the right pieces together"*

## Product Specifications

|                            |                                    |
|----------------------------|------------------------------------|
| Weight                     | kg                                 |
| Brand                      | XPR                                |
| Device-type                | Reader                             |
| Reader-and-card-technology | Mifare / Desfire CSN Only, Xsecure |
| Operating-temperature      | -30°C to 70°C                      |
| Power-requirement          | 10-15 VDC                          |
| Construction               | ABS                                |
| Frequency                  | 13.56 MHz                          |
| Mounting                   | Surface Mount                      |
| Protection-rating          | IP65, IK11                         |
| Series                     | Xpro                               |
| Versions                   | Standard, With X-Secure            |
| Form-factor                | Mullion                            |