



www.smartRdistribution.com orders@smartRdistribution.com

EAT-KIT-80HE-VP Scantronic 80HE Kits – 40-Zone Alarm System Kit with Wired or Wireless Keypad



Description

The Scantronic 80HE Kits offer a complete, Grade 2 intruder alarm solution in a single box, perfectly suited for residential and small-tomedium-sized commercial premises. The core of the system is the highly versatile hybrid (wired and wireless) control panel, which starts with 40 zones and is fully expandable up to 80 zones. The kit provides essential peripherals - PIRs, a door contact, and prox tags, and offers a choice between a traditional wired keypad (KIT-80HE-WKP) or a flexible wireless keypad (KIT-80HE-RKP). With a built-in Ethernet port, the 80HE panel comes ready for immediate, free-of-charge integration with the Eaton SecureConnect™ smart security cloud.

Technical Specifications:

- Control Panel: Scantronic 80HE (formerly i-on40H).
- Max Zones: Up to 80 zones total (starting at 40 inbuilt zones).
- Security Grade: EN50131 Grade 2.
- Connectivity: Built-in Ethernet for IP/Cloud communication (SecureConnect™).
- Keypad Types: Wired (KEY-KPZ) or Wireless (KEY-2R-KPZ). Both include 2 onboard zones and a prox tag reader.
- PIRs (DET-2R-PIR): Wireless, Grade 2 protection, Pet tolerant (up to 25kg), approx. 5-year battery life.
- Communication Protocol: Scantronic Secure Radio (SSR) for secure, bidirectional encrypted wireless communication.
- Kit Contents: 1x 80HE Panel, 1x Keypad (Wired or Wireless Please select when ordering), 3x Wireless PIRs, 1x Wireless Door Contact, 5x Proximity Tags.



Smart R Distribution Limited

Smart R House · 13 Moonhall Business Park · Helions Bumpstead Road Haverhill · Suffolk · CB9 7AA · England Phone UK: 01440 704 387 Phone Int'l: +44 1440 704 387

"Putting the right pieces together"



01440 704 387

www.smartRdistribution.com orders@smartRdistribution.com

Product Specifications

Weight	kg
Brand	Eaton, Scantronic
Device-type	Alarm System Kit
Grading-compliance	Grade 2
Connection-type	Wired, Wireless
Operating-temperature	-10°C to 55°C
Kit	Yes

