

**1256****ACTUATOR RELAY. SIMPLEBUS 1 AND 2**

Intelligent Simplebus device for controlling a relay on board (12÷24 VAC/VDC - 10A max). For use and programming of the function required, follow the indications given in the technical documentation. It can be used in Simplebus system. Power supply: 12 VAC or 20 VDC. Dimensions: 66X85X35mm (4 DIN modules). Line branch terminal art. 1214/2C in equipment.



**1256**

## ACTUATOR RELAY. SIMPLEBUS 1 AND 2

### COMPATIBLE SYSTEMS

Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes
Audio Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 1	Yes

### ELECTRICAL CHARACTERISTICS

Type of power supply	External power supply
----------------------	-----------------------

### HARDWARE FEATURES

Number of outputs (n°)	1
Type of outputs	Relay (C-NO-NC, 10A@12÷24 VAC/VDC)

### GENERAL FEATURES

CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)
Type of finishing materials	ABS
Product color	White RAL9010
Depth (mm)	85
Height (mm)	35
Width (mm)	66

### MAIN FEATURES

Operating temperature (°C)	-10 ÷ 40
Operating humidity (RH max) (%)	25 ÷ 95
DIN rail mounted	Yes
DIN modules (no.) (n°)	4



**1256**

## ACTUATOR RELAY. SIMPLEBUS 1 AND 2

### MAIN FEATURES

Maximum current absorption (mA)	50
---------------------------------	----