



Scan the QR code or link to the address below to find a list of datasheets to all products and other support information.

<https://www.tm-readers.com/downloads.htm>



Overview

The RX2 advanced access control reader is an elegant and slimline unit, designed particularly for upgrading from magnetic stripe card readers. Having a footprint which will cover one of the most popular magnetic stripe reader on the market, and a backplate with fixing centres to match, this reader will have little or no cosmetic impact to the wall finish.

The combination of an integral speaker, RGB LED and audible buzzer provides a flexible platform to give the right user interface configuration for your project.



Mechanical

Dimensions	144 x 54 x 21 mm (5.7 x 2.1 x 0.8 inches)
Housing	Moulded polycarbonate
Mounting	Suitable plain surface
Fixing	4mm., max' diameter



Environmental

Operating temp'	-35°C to +66°C
Humidity	85±5% at 30±2°C (86±3°F)
Ingress	IP67
Impact	IK10
Flammability	UL94V-0



Electrical

Voltage	see table below
Current	see table below
Data Voltage	Rest >4Vdc / Active <1Vdc
Data output	see table below
Indication	1 RGB LED
Sounder	Integral speaker
Termination	screw terminal connection block




Reader Models are sold as customer-specific configurations.

Please call +44 (0) 1495 751 992 to discuss your custom configuration or LEGIC® reader requirements.

* READER MODEL	Frequency	Current mA	Voltage Vdc	Technology	Optical tamper	Wiegand Clock & Data	OSDP	FCC	UL294
RX200	125 kHz	115	5 - 12	125kHz EM variants		•			
RX280PLUS	13.56 MHz 125 kHz	200	5 - 12	MIFARE® Sector + 125kHz		•		•	•
RX290B	13.56 MHz 125 kHz 2.4 GHz	75	10 - 16	MIFARE®DESFire® LEGIC® + 125kHz Bluetooth® ready	•	•	•	•	•

*certifications not available to all reader models.



The **RX2** reader offers a choice of technologies, and a range of security levels from 125kHz through MIFARE®Sector and LEGIC® encryption multiple technology access control ... all the way up to a **high-end** security level option using the **RX290B** reader model.

The **RX290B** boasts multiple technologies embedded in its hardware and firmware, providing a 13.56MHz MIFARE®DESFire® platform, having state-of-the-art security and privacy. The reader employs LEGIC® 13.56MHz contactless smart technology, with its tightly integrated LEGIC RF Standard. In addition, the reader can also be used for 125kHz access control systems, including other widely used 125kHz technologies such as:

- KANTECH
- FARPOINTE
- AWID
- CASI
- EM variants

Key features

- Multi-technology
- UK design and manufacture
- Black high gloss finish
- Slim profile
- RGB LED
- Fully encapsulated electronics
- Optical tamper switch (see table above)
- Wide range of output formats
- Read range up to 10cm (4 inches)
- 5 years limited warranty



All copyrights © and trademarks ® / ™ are acknowledged and remain the property of their respective owners.

The Bluetooth word, mark and logo are registered trademarks of Bluetooth SIG, Inc.

'MIFARE', 'MIFARE Classic' and 'MIFARE DESFire' are trademarks of NXP B.V.

RXSERIES © Third Millennium Systems Ltd
registered in England & Wales No. 3199053

Third Millennium Systems Ltd.
18 / 19 Torfaen Business Centre
Panteg Way New Inn PONTYPOOL NP4 0LS United Kingdom

100-03062-RX2-D E&OE SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

tel: +44 (0) 1495 751 992 web: www.tm-readers.com contact: info@tm-readers.com